

OXALWASH

Train exterior wash optimised for removal of iron staining



OXALWASH has been specifically formulated to clean and restore train carriages and other rolling stock by removing dirt, oil and rust in one application.

ADVANTAGES

Oxalwash rapidly removes dirt, oil and grime from surfaces.

Oxalwash dissolves brake/iron dust particles and removes iron stains from paintwork, vinyl and glass.

Rinses freely, with no scale residues.

Contains no mineral acids, will not damage concrete sleepers, floors or mortar.

Enhances shine on new or dulling paintwork, vinyl coatings and glass.

Will not damage glass.

Specifically formulated for use within the rail industry.

Highly concentrated and very economical in use.

TYPICAL APPLICATIONS

- Suitable for cleaning locomotives, carriages, freight wagons, tankers, trams and underground trains.
- An excellent fallout remover which will remove iron deposits from vehicle paintwork, window frames, cladding or wherever they may occur.
- Not to be used in automatic washing plants.

APPLICATION INSTRUCTIONS

Apply Oxalwash via brush or swab.

Typically used at a 1:40 dilution, for light soiling Oxalwash may be diluted up to 1:100. For heavy deposits use at 1:30.

Allow a short contact time, agitate and rinse with clean water.

Dilute with demineralised water.



OXALWASH

Train exterior wash optimised for removal of iron staining



TECHNICAL DATA

APPEARANCE	Slightly Viscous Liquid
COLOUR	Brown to Straw
ODOUR	Mild acidic
SOLUBILITY	Soluble in water
RELATIVE DENSITY	1.05 @ 25 °c
pH (concentrate)	1-2
PACK SIZES	1000, 210 and 20 litres

The values are typical of normal production and should not be taken as a specification.

PRECAUTIONS

Avoid spilling, skin and eye contact. Wear appropriate impervious protective clothing and eye protection when washing rolling stock. For automatic wash plants and pressure sprayers, demineralised water must be used to prevent mineral build up in the equipment.

ACCREDITATIONS & REGISTRATIONS

PPG Automotive Finish tested

4Rail Approved

UK Rail Approved Cat No. 007/007331 (20 Litre)
UK Rail Approved Cat No. 007/007316 (210 Litre)
UK Rail Approved Cat No. 007/007317 (1000 Litre)

STORAGE PRECAUTIONS

Keep containers tightly closed. Store at moderate temperatures in dry, well ventilated area.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



THICKENED OXALWASH

A ready to use thickened version of Oxalwash to provide increased contact time on heavy deposits



ECOWASH AUTOSHINE

Frequent use train exterior wash



TRAILERWASH

Powerful soil remover and degreaser



UNIVERSAL POWERWASH

A powerful heavy duty alkaline cleaner and degreaser

