

THICKENED OXALWASH

Viscous exterior train cleaner for the removal of heavy soiling and iron deposits



THICKENED OXALWASH is specifically formulated to clean train carriages and other rolling stock in order to remove dirt, oil and ferrous staining.

This thickened version of Oxalwash enhances cling and allows increased contact times on areas of heavy soiling.

ADVANTAGES

Viscous formula enhances cling, reduces run off, and provides extended contact times for areas where soil build-ups are particularly high.

Ready to use formula requires no mixing or dilution.

Thickened Oxalwash dissolves brake/iron dust particles, removing iron stains from paintwork, vinyl and glass.

Contains no mineral acids and will not damage concrete sleepers, floors or mortar.

Will not damage glass.

Rinses easily.

Specifically formulated for use within the rail industry

TYPICAL APPLICATIONS

- Suitable for cleaning locomotives, carriages, freight wagons, tankers, trams and underground trains.
- Ideal for periodic deep cleaning operations.
- Also an excellent fallout remover which will remove iron deposits from vehicle paintwork, window frames and cladding.
- Thickened Oxalwash is designed for manual application to areas where staining and soiling is particularly heavy.

APPLICATION INSTRUCTIONS

Use undiluted. Apply by brush or mop to the surface. Allow a few minutes contact time to penetrate and release iron residues and dirt. Agitate periodically to loosen soil. Rinse thoroughly with clean water.



THICKENED OXALWASH

Viscous exterior train cleaner for the removal of heavy soiling and iron deposits



TECHNICAL DATA

APPEARANCE	Viscous liquid
COLOUR	Colourless/pale straw
ODOUR	Mild acidic
SOLUBILITY	Soluble in water
RELATIVE DENSITY	1.01 @ 20 °c
pH (concentrate)	1-2
FLAMMABILITY	Non Flammable
PACK SIZES	1,000 and 20 litres

PRECAUTIONS

Avoid spilling, skin and eye contact. Wear appropriate impervious protective clothing and eye protection when washing rolling stock. Refer to Safety Data Sheet (available on request).

ACCREDITATIONS & REGISTRATIONS

UK Rail Cat No's:
007/000027 20 litre
007/000026 1000 litre

STORAGE PRECAUTIONS

Keep containers tightly closed. Store at moderate temperatures in dry, well ventilated area.

RELATED PRODUCTS



OXALWASH

Train exterior wash optimised for removal of iron staining.



ECOWASH AUTOSHINE

Frequent use train exterior wash



TRAILERWASH

Powerful soil remover and degreaser



UNIVERSAL POWERWASH

A powerful heavy duty alkaline cleaner and degreaser

