

DELTA

Fast breaking solvent degreaser for ship's bilges and interceptors



DELTA is a quick breaking degreaser that provides rapid cleaning of oil and general grime from a wide variety of hard surfaces. After rinsing with water, the resulting emulsion breaks quickly, providing rapid separation and segregation of oil and water phases in interceptors and oil and water separators. This assists in ensuring continued compliance with consent limits for waste discharge.

ADVANTAGES

Emulsifies grease, oil and fuel residues in ships bilges and oil tanks

Suitable for use in workshop parts washers, residues may be rinsed off with water

Not classified as flammable and contains no aromatic hydrocarbons

Separates rapidly in interceptors and oil and water separators for reduced environmental discharge

Suitable for use by marine operators, ship builders, port and harbour authorities

Ideal degreaser for use in production and maintenance degreasing

Powerful remover of heavy oils, heavy grease, tar and bitumen

Low odour

TYPICAL APPLICATIONS

Marine

- Emulsifies grease, oil and fuel residues from deck equipment, deck and superstructure, cargo holds, tanks and in workshop degreasing operations
- Breaks down oil and grease residues in ships bilges.

Industry

- Ideal degreaser for use in production and maintenance degreasing
- Powerful remover of heavy oils and greases, asphalt, tar and bitumen prior to maintenance inspection or repair of plant and equipment.
- Suitable for use in workshop parts washers

APPLICATION INSTRUCTIONS

Apply Delta undiluted via brush or low-pressure sprayer. Agitate stubborn deposits. Where required rinse with water, ideally with a pressure washer. Note waste must be segregated for separation via interceptor or oil and water separator. For ships bilges apply product undiluted, where appropriate brush or pressure wash residues from the bilge walls. Alternatively apply Delta undiluted and allow the ships natural rolling motion to break up oil and grease residues.

DELTA

Fast breaking solvent degreaser for ship's bilges and interceptors



TECHNICAL DATA

APPEARANCE	Liquid
COLOUR	Colourless to pale yellow
ODOUR	Mild solvent
SOLUBILITY	Miscible with water
RELATIVE DENSITY	0.80
FLASH POINT (°C)	70 CC (Closed cup)
VOC CONTENT	788 g/L
OIL SEPARATION	<25 ppm (oil in wastewater after 24 hours)
PACK SIZE	5 litre, 20 litre, 500ml aerosol

PRECAUTIONS

Keep away from heat, sparks and open flame. Provide good ventilation.

APPROVALS & REGISTRATIONS

Scientifics Approved

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well-ventilated area.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



HDD
Heavy duty emulsifiable solvent degreaser



UNIVERSAL POWERWASH
A powerful heavy duty alkaline cleaner and degreaser



CITROL
Microemulsion cleaner and degreaser



ISO 14001:2004
Cert No. 1263



OHSAS 18001
Occupational Health and Safety Management



ISO 9001:2008
Quality Management



Cert: 310314001