LOTOXANE® FAST

A faster drying Lotoxane® variant which evaporates 3 times faster than standard Lotoxane®





LOTOXANE® FAST is a high quality solvent degreaser that offers professional users a versatile alternative to more hazardous products. It is widely approved by major OEMs for production and maintenance cleaning.

ADVANTAGES

Low odour

Reduced hazard to user

Helps in reducing VOCs'

Can be recycled for reduced consumption

TYPICAL APPLICATIONS

- Removal of oils, greases, machining fluids and general contamination in manufacturing process
- → Pre cleaning prior to NDT or inspection
- Removal of temporary protective coatings/dewaxing; Cleaning prior to painting or bonding operations
- Degreasing of machinery, components and assemblies during maintenance and repair
- Cleaning electrical and electronic equipment
- → De-watering components and electrical systems

APPLICATION INSTRUCTIONS

Manual Cleaning: Apply to the surface by spray or paintbrush. Agitate stubborn deposits if required with a stiff brush and wipe away residues with a clean cloth. Suitable for use with most types of degreasing stations.

Dip tank: Allow adequate contact time, typically 10 - 15 minutes, then remove and allow to drain, agitate components if required. To reduce losses from the tank it is advised that a close fitting lid is used.

Parts washers: Cold use only. Leave components to air dry naturally.

 $\ensuremath{\textbf{Note}}\xspace$: Drying times can be improved by wiping away excess or forced air drying.



LOTOXANE® FAST

A faster drying Lotoxane® variant which evaporates 3 times faster than standard Lotoxane®



TECHNICAL DATA

ODOUR	Low odour
SOLUBILITY	Insoluble in water
FLAMMABILITY	Flammable liquid and vapour
FLASH POINT	40°C
PACK SIZES	 ✓ 500ml trigger ✓ Wipes (x85) ✓ 5 litre ✓ 20 litre ✓ 210 litre

LIMITATIONS

Not suitable for vapour degreasing. For heavier duty applications consider Lotoxane HD or Fastklean. When faster evaporation is required consider Lotoxane XF or Lotoxane Triple F.

ACCREDITATIONS & REGISTRATIONS

- → Rolls Royce CSS255 Type A,B,D
- **→** Rolls Royce OMAT 1/257H
- Pratt and Whitney SPOP 208 Solvent Wiping- SPMC 216-1 solvent liquid and SPMC 216-2 for solvent wipes
- **→** ARP1755B

HEALTH AND SAFETY, STORAGE AND PRECAUTIONS

Refer to Safety Data Sheet (available on request)

ALSO AVAILABLE



LOTOXANE®The trusted, safe solution for professional degreasing



LOTOXANE® XF
A faster drying Lotoxane® variant
which evaporates 6 times faster than
standard Lotoxane®.



LOTOXANE® TRIPLE F
A faster drying Lotoxane® variant which
evaporates 15 times faster than standard
Lotoxane®.



LOTOXANE® HD
Safe non-flammable solvent degreaser
with enhanced degreasing ability.



















