

# LOTOXANE® XF

A faster drying Lotoxane® variant which evaporates 6 times faster than standard Lotoxane®



**LOTOXANE® XF is a high quality solvent degreaser that offers professional users a versatile alternative to more hazardous products. It is widely approved by major OEMs for production and maintenance cleaning.**

## ADVANTAGES

Reduced hazard to user

Flash point 27°C

Effectively replaces thinners, MEK, toluene and other more hazardous solvents

Helps in reducing VOCs'

## TYPICAL APPLICATIONS

- Removal of oils, greases, machining fluids and general contamination in manufacturing process
- Pre cleaning prior to NDT or inspection
- Removal of temporary protective coatings/de-waxing; Cleaning prior to painting or bonding operations
- Degreasing of machinery, components and assemblies during maintenance and repair
- Cleaning electrical and electronic equipment
- De-watering components and electrical systems

## APPLICATION INSTRUCTIONS

**Manual Cleaning:** Apply to the surface by spray or paintbrush. Agitate stubborn deposits if required with a stiff brush and wipe away residues with a clean cloth.

**Dip tank:** Allow adequate contact time, typically 10 - 15 minutes, then remove and allow to drain, agitate components if required. To reduce losses from the tank it is advised that a close fitting lid is used.

**Parts washers:** Cold use only. Leave components to air dry naturally.

**Note:** Drying times can be improved by wiping away excess or forced air drying



# LOTOXANE® XF

A faster drying Lotoxane® variant which evaporates 6 times faster than standard Lotoxane®



## TECHNICAL DATA

ODOUR	Low odour
SOLUBILITY	Insoluble in water
FLAMMABILITY	Flammable liquid and vapour
FLASH POINT	27°C
PACK SIZES	<ul style="list-style-type: none"><li>➤ 300ml aerosol</li><li>➤ 5 litre</li><li>➤ 20 litre</li><li>➤ 210 litre</li></ul>

Other pack sizes available on a made to order basis.

## LIMITATIONS

Not suitable for vapour degreasing. For heavier duty applications consider Lotoxane HD or Fastklean. When faster evaporation is required consider Lotoxane Triple F.

## ACCREDITATIONS & REGISTRATIONS

- Rolls Royce CSS255 Type A,B,D
- Rolls Royce OMAT 1/257H
- BAE R10-6027 (cleaning - cold solvent - critical applications)

## HEALTH AND SAFETY, STORAGE AND PRECAUTIONS

Refer to Safety Data Sheet (available on request)

## ALSO AVAILABLE



### LOTOXANE®

The trusted, safe solution for professional degreasing.



### LOTOXANE® FAST

A faster drying Lotoxane® variant which evaporates 3 times faster than standard Lotoxane®.



### LOTOXANE® TRIPLE F

A faster drying Lotoxane® variant which evaporates 15 times faster than standard Lotoxane®.



### LOTOXANE® HD

Safe non-flammable solvent degreaser with enhanced degreasing ability.

