

SUPERSOLVE AS

Electronic contact cleaner for critical surfaces



SUPERSOLVE AS aerosol is an exceptionally clean, fast evaporating and low odour solvent degreaser, which dries rapidly to a residue free finish. Supersolve AS has been formulated with highly refined solvents for excellent compatibility with circuit boards, insulating materials and electronic components.

ADVANTAGES

Rapid dry and zero residue make Supersolve AS ideal for surface preparation prior to bonding, painting and inspection

Refined formulation will not damage sensitive equipment or components, flammability is suppressed by the use of non flammable propellants

Tested and approved for aerospace applications

Provides effective removal of oils and particulates

Low odour

TYPICAL APPLICATIONS

- Use Supersolve AS for cleaning electrical and electronic assemblies, motors solenoids and switchgear in aerospace, manufacturing and food processing applications
- Supersolve AS is a highly effective NDT (non-destructive testing) Stage 1 Cleaner for routine maintenance or quality inspections.
- Superb for the preparation of surfaces prior to bonding, painting or coating
- Exceptional spot cleaner for removal of oil spots from delicate fabrics, carpets and upholstery
- Ideally suited for all manufacturing and maintenance environments

APPLICATION INSTRUCTIONS

Electrical and electronic cleaning

1. Do not apply to live electrical circuits or hot surfaces.
2. Switch off electrical supply.
3. Shake can.
4. Spray as required to flush oil and grease from the system.
5. Allow to air dry fully before reconnecting power.

Component cleaning and degreasing

1. Shake can.
2. Spray liberally onto the component.
3. Agitate stubborn residues with a brush or wipe away with a lint free cloth.
4. Re-apply if required.
5. Allow to dry.



SUPERSOLVE AS

Electronic contact cleaner for critical surfaces



TECHNICAL DATA

APPEARANCE	Aerosol
ODOUR	Solvent
COLOUR	Water - white
PACK SIZE	400ml Aerosol

PRECAUTIONS

Avoid inhalation of vapours/spray and contact with skin and eyes. Keep away from heat, sparks and open flame. Provide good ventilation.

STORAGE PRECAUTIONS

Store at temperatures between 4°C and 40°C. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



QED

Quick dry electrical & workshop degreaser



LOTOXANE® FAST

A faster drying Lotoxane® variant which evaporates three times faster than standard Lotoxane®



FASTKLEAN

Fast drying electrical component and machinery cleaner and degreaser



SUPERSOLVE CC

Premium heavy duty contact cleaner for critical surfaces

